10. DISTRIBUTION STATEMENT

Security Classification

AD-742517

Unclassified
26. GROUP
and System Engineering Test

• REPORT DATE 20 April 1972	78, TOTAL NO. OF PAGES	7b. NO. OF REFS		
Se. CONTRACT OR GRANT NO.	Se. ORIGINATOR'S REPORT NU	Se. ORIGINATOR'S REPORT NUMBER(S)		
è PROJECT NO.	TOP 10-2-072	TOP 10-2-072		
c. AMCR 310-6	99. OTHER REPORT NO(8) (An)	98. OTHER REPORT NO(8) (Any other numbers that may be assigned this report)		
d.				

Approved for puolic release; distribution unlimited.

12. SPONSORING MILITARY ACTIVITY
Headquarters
U.S. Army Test and Evaluation Command
Aberdeen Proving Ground, Md. 21005

Describes a method for evaluation of heating equipment operational and performance characteristics... Identifies supporting tests, facilities, and equipment required. Provides procedures for heating capacity and smoke tests... Applicable to space, radiant, portable nonduct and duct type heaters.

Reproduced by NATIONAL TECHNICAL INFORMATION SERVICE Springfield, Va. 22151

9

UNCLASSIFIFD

Heater Ventilation System Environmental control set	Security Classification						
Heater Ventilation System Environmental control set	14. KEY WORDS						
Ventilation System Environmental control set		HOLE	- W T	4768	W T		:
Ventilation System Environmental control set	Heater						
Environmental control set	•	1					
	Environmental control set	1					
]			
		l l		1	}		
				•	1		
		1	l	ł	,	1	ţ :
		İ	l		ļ		
							ļ
		1]	Ì]	1]
]]	1	1
		1	1	}	1	1	1
		1		1		1	
			l	l			1
			İ	l	1	1	1
			1	1	1	1	1
		1	1	1	1	1	1
		1	İ		1	1	,
		l	ł	l	1	1	l
		l	1			1	
]	1	1	}		1
		l		1	1	1	1
		1	1	1	1	1	1
						l l	1
			1	1	1		ł
		i	1	1	l		1
	•	1	1	1	1	j	1
		1	1	1	1		1
		1		1	1		1
		1	l	1	į.	1	l
	and the compact of the contract ,,,		.:).			1	
			1]	1		1
		1	1	1	İ	1	1
		- [}	1	1	1	1
		-			1	1	
		1			1	1	i
			1	1			1
		1		1		1	
		1	1	1	1	1	1
				1		1	
		-	1		1	1	1
		1	1	1		1	
		}	1	1		1	1
			1	}	1	1	1
			1				<u> </u>

UNCLASSIFIED
Security Classification

U.S. ARMY TEST AND EVALUATION COMMAND SYSTEM ENGINEERING TEST OPERATIONS PROCEDURES

AMSTE-RP-702-109
*Test Operations Procedure 10-2-072

20 April 1972

!	•
Ch	
S	
4:	
V	

HEATING EQUIPMENT

Section I.	GENERAL	Paragraph	Page
	Purpose and Scope	1	1
	Background		1
	Equipment and Facilities		2
II.	TEST PROCEDURES		
	Supporting Tests	4	2
III.	SUPPLEMENTARY INSTRUCTIONS		
-	Capacity	5	4
	Smoke Test		4

SECTION I GENERAL

APPENDIX. REFERENCES

- 1. Purpose and Scope. This TOP describes test procedures for evaluating the operational and performance characteristics of heating equipment. Equipment covered includes: space, radiant, portable nonduct and duct type heaters. From the tests listed in Section II, the test director can select those that will satisfy the requirements for the particular test item and the particular test type (i.e., engineering test, initial production test, etc.). Test objectives are to determine conformance of the test items to QMR, MN or other suitability criteria. For initial production tests, scope will be in accordance with the contractual provisions of the applicable military specifications and suitability criteria established by the test directive. This document provides for simulated environmental testing but does not include service testing or environmental testing at climatic test sites.
- 2. <u>Background</u>. The requirement of nonduct heaters to support field operations of the Armed Services entail a variety of problems and a continuing challenge in research. To fulfill these heater requirements, new types of heaters are constantly being developed and the existing heaters are being improved or modified to support the military requirements brought about by the new tectical and logistical concepts of

*This TOP supersedes MTPs 10-2-070 (24 Jul 67), and 10-2-071 (21 Mar 68), including all changes.

Approved for public release; distribution unlimited.

C IN S 1215 DEVICE LITTED

PUBLICATION NO.

warfare. These new and improved heaters then are the results of projects to correct deficiencies, to improve upon operation, and to reduce cost without changing general operational characteristics. The heaters must be capable of efficiently performing their required function in the field for which they have been developed or modified.

3. Equipment and Facilities. Equipment and facilities required are defined in the documents listed in Section III and Section III.

SECTION II TEST PROCEDURES

4. Supporting Tests. Subtests (generally in preferred order of completion with respect to high-risk, short duration) to be considered in formulating a test plan are listed below with references.

TEST SUBJECT TITLE

a. Pre	-operational Inspection	10-3-500
(1)	•	10-2-501
(2)	Photographic Coverage	7-3-519
b. Phy	sical Characteristics	10-2-500
c. Saf	ety	10-2-508
d. Per	formance	
(1)	Coal Fired Space Heater	MIL-H-11219B
	4.5	Para 4.2
	(a) Capacity (Refer to para 5)	
	(b) Smoke Test (Refer to para 6)	
(2)	Electric Space Heater	MIL-H-19910
		Paras 4.5.2.
		4.5.3
4	Capacity (Refer to para 5)	
(3)	Multifuel Space Heater	MIL-H-52204B
311	•	Paras 4.5.2.4.
DEC BUSH SEETING C		4.5.2.6,
HANKERS CITINGES		4.5.2.8
PRESSENCE TO SEE THE PROPERTY OF THE PROPERTY	(a) Capacity and Airflow	Para 4.5.2.1
	(b) Controls and Safety Operation	Para 4.5.2.3
(4)	Duct Heaters	MIL-H-52230A
and definition representations and		
		Paras 4.5.2.6,
tier, tien, their Section		4.5.2.8,
	(a) Connector and Admilian	4.5.2.10
\(\)	(a) Capacity and Airflow	Para 4.5.2.1
M	(b) Controls and Safety Operation	Para 4.5.2.3
1		

		TEST SUBJECT TITLE	PUBLICATION NO.
e.	Envir	conmental Testing	
	(1)	Altitude	MIL-STD-810B
			Merhod 500
	(2)	Temperature	Method 501
	(3)	Sunshine	4-2-826
	(4)	Rain	2-2-815
	(5)	Humidity	4-2-820
	(6)	Fungus	4-2-818
	(7)	Salt Fog	MIL-STD-810B
			Method 509
	(8)	Dust Test	Method 510
	(9)	Vibration	4-2-804
			MIL-H-52230A
			Para 4.5.2.2.7
	(10)	<u> </u>	4-2-602
		Shock	MIL-H-52204B
			Para 4.5.2.2.7
	(11)		MIL-STD-461A
		Characteristics	Notice 4
			MIL-STD-462
			Notice 3
			Methods CE02,
			REO5
f.	Trans	sportability	
	(1)	₹	10-2-503
	(2)	•	7-2-515
g.		r Factors Evaluation	10-2-505
		i-level	
	(1)	Space Heater	MIL-H-52204B
			Para 4.5.2.5
	(2)	Duct Heater	MIL-H-52230A
_			Para 4.5.2.5
h.		ability	AMCP 702-3
	Confi	idence Intervals and Sampling Size	3-1-002
i.	Durab	oility (Endurance Testing)	10-2-502
	Mad A	hannes Franklan	10 2 507
j.	maint	tenance Evaluation	10-2-507
k.	Value	e Analysis	USAMC SUPPL 1
			to AR 11-26

SECTION III SUPPLEMENTARY INSTRUCTIONS

5. Capacity.


- a. Objective. To determine the heating characteristics of the test item.
- b. Method. The test item is mounted or installed in the center of the test area. Thermocouples or mercury thermometers are positioned about the test item as shown in figure 1. The test item is then operated for one hour at test conditions to insure temperature stabilization and uniform operation. After stabilization, the required data is recorded every 15 minutes for a total of not less than five complete sets of data. These procedures are repeated for test item operating conditions of one-quarter, one-half, three-quarters and maximum output.

c. Data Required.

- (1) Test item nomenclature and type.
- (2) Temperature recorded at the installed thermocouples or thermometers.
- (3) Fuel weight in pounds and ounces or power input in volts, watts and amps used during recorded test periods.
- (4) Flue-gas temperature, °F (read within one inch of where flue-gas analysis sample is taken), if applicable.
- (5) Flue-gas analysis, if applicable (refer to paragraph 4.5.2.1.6, MIL-H-52204B (appendix)).
- d. Analytical Plan. The indicated and measured outputs and efficiencies are computed and compared with the requirements of the MN to determine conformance to specifications.

6. Smoke Test,

- a. Objective. To determine that the test item does not emit smoke which is hazardous to health and welfare of personnel.
- b. Method. A sample of gases emitted from the test item is collected and subjected to a laboratory analysis to determine its content. Photographs are taken of any visible gas emissions (smoke).



- NOTE: 1. Each dot represents an increment/measurement at which a thermocouple or thermometer will be installed away from the heater.
 - 2. "X" is the thermocouple in the flue, when applicable.
 - 3. Drawing is not to scale.

Figure 1. Example of Arrangement of Thermocouples or Thermometers.

- c. Data Required.
 - (1) Test item nomenclature and type.
 - (2) Volume of gas sample.
 - (3) Photographs of visible gas emissions (smoke).
 - (4) Laboratory analysis of gas sample.
- d. Analytical Plan. The contents of the analyzed gas sample and the photography of the visible gas emissions are compared with the requirements of the MN to determine conformance to specifications.

Recommended changes to this publication should be forwarded to Commanding General, U.S. Army Test and Evaluation Command, ATTN: AMSTE-ME Aberdeen Proving Ground, Maryland 21005. Technical information related to this publication may be obtained from the preparing activity, Commanding Officer, Aberdeen Proving Ground, ATTN: STEAP-MT-DM, Aberdeen Proving Ground, Maryland 21005. Additional copies of this document are available from the Defense Documentation Center, Cameron Station, Alexandria, Virginia 22314. This document is identified by the accession number (AD No.) printed on the first page.

APPENDIX REFERENCES

- 1. AR 70-38, "Research, Development Test, and Evaluation of Materiels for Extreme Climatic Conditions."
- 2. USAMC Supplement 1 to AR 11-26, "Value Engineering."
- 3. AMCP 702-3, "Quality Assurance Reliability Handbook."
- 4. MIL-STD-461A, "Electromagnetic Interference Characteristics, Requirements for Equipment", including notices 1 thru 4.
- 5. MIL-STD-462, "Electromagnetic Interference Characteristics, Measurement of", including notices 1 thru 3.
- 6. MIL-STD-810B, "Environmental Test Methods", including notices 1 thru 4.
- 7. MIL-H-11219B, "Heater, Space, Non-Electric (Magazine Type, Coal-Fired, 50,000 BTU Per Hour)."
- 8. MIL-H-19910, "Heater, Space, Electric."
- 9. MIL-H-52204B, "Heaters, Space; Multi Fuel, With Blower, 15,000 BTU/Hr."
- 10. MIL-H-52230A, "Heaters, Duct-Type, Portable: 150,000 BTU/Hr."